



## Cactus® Double Coated Film Tape

Technical Data Sheet No. L2940

### Product Information

Cactus® Double Coated Film Tape L2940 is an acrylic solvent-based pressure sensitive adhesive tape which offers quick bonding result with exceptional temperature, chemical and UV resistance.  
(UL Approved - File No. MH19350)

### Composition & Physical Properties

Adhesive System	: Solvent Acrylic	Tape Thickness	: 5 mil (0.125 ± 0.005mm)
Carrier	: 1/2 mil PET Film	Loop Tack FINAT-9	: 63 oz/inch (over 1.8 kg / 25 mm)
Liner Thickness	: 3 mil	Peel Adhesion PSTC-3	: 70.4 oz/inch (over 2.0 kg / 25 mm)
Liner Material	: Glassine Paper	Shear Strength PSTC-7	: Over 24 hrs with 70.4 oz loading on 25mm x 25mm 77°F
Liner Density	: #60 (90 g/m <sup>2</sup> )	Heat Resistance:	: Over 24 hrs with 17.6 oz loading on 25mm x 25mm at 176°F
Liner Color	: Mustard	Service Temperature	: -4°F ~ 356°F (-20°C ~ 180°C)
Tape Color	: Clear		

### Applications

- Metal and plastic signage attachment
- High temperature splicing
- Mounting of PVC profiles in the office equipment industry
- Fastening and laminating parts in electronic devices (in die-cut pieces)

### Disclaimer and Limitation of Liability

In no event shall V. Himark USA and its employees be liable for any direct or indirect, special, incidental or consequential damage resulting from the use of this product. Therefore, it is strongly recommended that the user performs a test application first to determine the suitability of this product for the intended method of application.