



Cactus® Double Coated Foam Tape

Technical Data Sheet No. R2208

Product Information

Cactus® Double Coated Foam Tape R2208 is a solvent-based rubber pressure sensitive adhesive tape that offers very high shear strength and good initial tack. Ideal for various mounting, joining and sealing applications. Reinforced with White 6 PCF cross-linked polyethylene foam, providing excellent adhesion to irregular surfaces and various substrates.

Composition & Physical Properties

Adhesive System	: Solvent Rubber	Tape Thickness	: 1/32" (0.8 ± 0.1mm)
Carrier	: Polyethylene Foam	Tack	: J. Dow No. 7
Foam Density	: 6 PCF	Peel Adhesion	: PSTC-3 123 oz/inch (over 3.5 kg/25mm)
Liner Thickness / Density	: 3 mil #60 (90 g/m ²)	Shear Strength PSTC-9	: Over 100 hrs with 70.6 oz loading on 1" x 1" (2.0 kg/25mm x 25mm) bonding 2 stainless steel plates at 77°F (25°C)
Liner Material	: Glassine Paper	Service Temperature	: 14°F ~ 122°F (-10°C ~ 50°C)
Liner Color	: White	Tape Color	: White

Applications

- Excellent for bonding heavy-duty hanger hooks in indoor environments
- For joining and mounting of nameplates, plastics, mirrors and emblems
- For indoor mounting and bonding of Point of Purchase (POP) displays and graphics.
- For fixing of plastic or metal items e.g. stationeries, kitchenware, bathroom accessories, etc

Disclaimer and Limitation of Liability

In no event shall V. Himark USA and its employees be liable for any indirect, special, incidental or consequential damage resulting from the use of this product. Therefore, it is strongly recommended that the user performs a test application first to determine the suitability of this product for the intended method of application.