

**Cactus® Double Coated Tissue Tape** 

**Technical Data Sheet No. S248P** 

## **Product Information**

Cactus® Double Coated Tissue Tape S248P is an acrylic solvent based adhesive tape that offers good tack to lower energy surface substrates like plastics of PS, ABS, PC and PP. Has good resistance to solvents, heat and chemicals. Ideal for splicing and laminating applications.

Composition & Pl	cal Properties	
Adhesive System	Solvent Acrylic Tape Thickness	: 4.0 mil (0.10 ± 0.005 mm)
Carrier	Tissue Tack	: J Dow No. 16
Liner Thickness	5 mil Peel Adhesion PSTC-3	: 49.4 oz/inch (1.4 kg/25mm)
Liner Material	VHK Labeled Kraft Shear Strength PSTC-7	Over 24 hrs with 35.3 oz loading on 1" x 1" : (1.0 kg/25mm x 25mm) bonding 2 stainless steel plates at 77°F (25°)
Liner Density	#80 (130 g/m²) Heat Resistance	Over 24 hrs with 17.6 oz loading on 2 mm x 25mm at 176°F (80°C)
Liner Color	White Service Temperature	: -8°F ~ 212°F (-40°C ~ 100°C)
Tape Color	White	

## **Applications**

- For splicing plastic film, paper, foil, etc
- · Fastening of nameplates, signs, labels and emblems
- Laminating of texture, felt and objects with uneven surfaces

## Disclaimer and Limitation of Liability

In no event shall V. Himark USA and its employees be liable for any direct or indirect, special, incidental or consequential damage resulting from the use of this product. Therefore, it is strongly recommended that the user performs a test application first to determine the suitability of this product for the intended method of application.

Copyright © 2014 V. Himark (USA) Inc., all rights reserved.

www.cactustape.com