



Cactus® Double Coated Film Tape

Technical Data Sheet No. B2980

Product Information

Cactus® Double Coated Film Tape B2980 is an ultra-thin acrylic solvent-based pressure sensitive adhesive tape which offers a high adhesion level and good shear resistance. Ideal for kiss and die cutting processes, and for laminating and fastening applications of electronic devices. Made with high-performance adhesive and provides high grab tack and reliable bonding strength where quick fastening results are required.

Composition & Physical Properties

Adhesive System	: Solvent Acrylic	Tape Thickness	: 2.3 mil (0.06 ± 0.05 mm)
Carrier	: 0.5 mil PET Film	Tack	: J. Dow No. 7
		Loop Tack	1.5 ↑
Liner Thickness	: 4.7 mil	180° Peel adhesion	: 1.5 ↑
Liner Material	: Bleached Kraft Paper	Shear Strength PSTC-7	: Over 24 hrs with 2.2 lbs loading on 1" x 1" (1.0 kg / 25mm x 25mm) bonding 2 stainless steel plates at 77°F (25°C)
Liner Density	: #74 (110 g/m ²)	Service Temperature	: -22°F ~ 194°F (-30°C ~ 90°C)
Liner Color	: Black	Tape Color	: Black

Applications

- Exceptionally thin film tape for bonding signs and panels made of metal or plastic
- Fixing and splicing of various substrates for convenient kiss and die cutting processes
- For laminating and fastening applications of electronic devices

Disclaimer and Limitation of Liability

In no event shall V. Himark USA and its employees be liable for any direct or indirect, special, incidental or consequential damage resulting from the use of this product. Therefore, it is strongly recommended that the user performs a test application first to determine the suitability of this product for the intended method of application.